



ColorBlend® Powder Release

Description:

Formulated to provide a non-stick barrier between colored surfaces and stamping tools. Allows a non-chemical bond between the surfaces for later removal by low pressure cleaning and brushing. This exposes the finished surfaces, leaving an antique look residue color.

Additions of iron oxide colors will result in a small amount of color to adhere to moist surfaces. This will produce an antique-like effect.

Methods vary in the use of this type of product and is intended for trained personnel to produce the intended professional look and results.

Available in several colors and/or clear non-tinted as a plain tool release.

Uses:

For producing stamping tools release when using *ColorBlend*® surface color hardeners. Used over plain concrete, in combination with integral colored concrete or combining release colors for an antique look over decorative finishes.

Limitations:

All finishes produced with release powders (colored or not) must be clear coated to provide durability. Always test a small area to ascertain the desired color result and installation technique.

Installation:

Broad-cast by hand at the rate of 2 to 3 pounds per 100 Sq./Ft. or until the surface is fully covered to allow a dry non-stick surface for the tools. After stamping, cover surfaces to be cured with a suitable unwrinkled Craft paper meeting ASTM C-171.

This will reduce evaporation that can result in surface plastic shrinkage cracks.

Packaging:

Available in 30 pound plastic pails, colored or plain.

Compliance:

Colors meet specification ASTM- C 979 for iron oxide pigments.

Finish and Clean-up:

Surfaces treated with the release powder can be washed off with low pressure water to remove as much of the release agent color as desired. Be careful to not remove the remaining antiquing effect that has bonded to the surfaces.

Finished surfaces should be allowed to air dry to see the desired results prior to clear sealing. When using clear release, all surface release should be removed prior to clear sealing. Clean tools and equipment with soap and water.

Product Safety:

Contains hydrophobic calcium and silica. Avoid breathing in dust. Use approved respirator and wear eye protection. In case of exposure, wash skin with soapy water and eyes with cool water. Seek medical help if irritation persists.

Color selection:


Available in 16 standard colors.

TOURNING
ESTER

Builders Construction Products
2761 NW 19th St, Pompano Beach, Fl. 33069
Tel: (954) 657-8812 Fax: (954) 657-8631
www.Buildercolor.com



We care about the environment

Builders 
CONSTRUCTION PRODUCTS

Warranty:

When product is used according to directions; warranty is limited to the refund of the purchase price if deemed defective at manufacture. Products exceeding their shelf life are excluded from this warranty. Products are intended for industrial professional use by competent tradesmen with sufficient knowledge and experience on their use, installation and product suitability.

Builders Construction Products shall not be liable to the purchaser or any third party for labor costs, direct or indirect, any consequential damages related or due to the use, suitability or installation of this product.

No other warranties are implied. No one is authorized, employees of Builders Const. Prods. or otherwise to make modifications or misrepresentations of any warranties, other than what is expressed or covered in this published document. Purchaser and or the end user agrees to assume all responsibility for use, transport and proper disposal of un-used product and packaging. Keep from the reach of children and pets.

Do not dispose in drainage systems, lakes or bodies of water. Review MSDS for additional health information.

www.BuildersColor.com