



ColorBlend[®] Concrete Stain

Description

ColorBlend[™] Stain & Cure is an Acrylic pigmented curing and sealing liquid emulsion designed to protect freshly finished colored concrete and to complement the colored surfaces by eliminating any color variation from inconsistent finishing, color deterioration due to un-cured surfaces, efflorescence damage, inconsistencies in substrate moisture and absorbency rates, staining, sun exposure, and a host of other factors affecting the concrete surface color when fresh or over time. Provides a soft finish when dry.

Uses & Limitations:

Use on fresh colored concrete surfaces as a color complement and curing, or over existing gray or colored concrete to repair, add or change the color. Product will produce a painted look and it is not supposed to replace integral or hardener type colored concrete systems in durability. This product is intended for its surface color enhancing and sealing qualities. Very durable when exposed to exterior surfaces.

Application and Surface preparation:

Apply to surfaces to be cured at the rate of 200 to 400 Sq./Ft per gallon, as soon as concrete has sufficiently hardened to support foot traffic without marring the surface. Do not dilute or puddle the product. A second coat can be applied after 7 to 14 days over freshly poured concrete. On existing concrete, clean all dirt and contaminants. Apply first coat to a dry surface to allow stain to penetrate. A second coat can be applied after the first coat has dried to the touch.

Coverage

Over light broomed concrete, the coverage will mostly average 200 to 400 Sq./Ft per gallon. Surface profile and absorbency will determine your true coverage. 2 coats are required for best results and color.

Packaging

Available in 5 gallon pails. Standard colors.

Safety, Clean up and Disposal:

Water based liquid Acrylic non-flammable emulsion. . Clean tools and equipment with soap and water. Keep away from children and pets. Wear eye protection and avoid prolonged skin contact. Dispose of product and containers responsibly.

Compliance:


ASTM 309, ASTM 1315-Type I, class A ASTM 3359
Method A VOC <250 gm./l.

Warranty: When product is used according to directions, warranty is limited to the refund of the purchase price if deemed defective at manufacture. This product is intended for industrial professional use by competent tradesmen. Builders Construction Products shall not be liable to the purchaser or any third party for costs of labor direct or indirect, incidental or consequential damages related to the use or suitability of this product. No other warranties are implied. Responsible disposal of used products and packaging is the responsibility of the purchaser and or end user.

Builders Construction Products
2761 NW 19th St, Pompano Beach, Fl. 33069
Tel: (954) 657-8812 Fax: (954) 657-8631



We care about the environment

Builders 
CONSTRUCTION PRODUCTS

TOP SECRET