



# Crystal Seal Gray

## Industrial Floor Sealer & Moisture Barrier

### **Description and Uses:**

Pigmented solvent based membrane forming gloss sealer that seals & enhances concrete and protects against moisture damage, abrasion, dirt and chemical attack. Provides an even Medium Gray non-fading color on 2 coats. Using new high performance acrylic polymers that do not yellow and last longer than conventional resins. Perfect to use on driveways and exposed areas. Stops vapor transmission. Resist most automobile Fluids and acids except brake fluid which will soften the surface. Used on warehouse floors, commercial storage places, garages, walkways, etc. Suitable for forklift traffic. First coat can be polymer textured (sold separately) for slip resistance.

### **Limitations:**

Product should be installed on clean, dry and fully cured concrete. A test should be performed prior to use to make certain the surface is not retaining vapors that will prevent adhesion. Test and area by taping a piece of clear plastic 2' X 2' with duct tape all around the plastic to seal the edges in an area of sun exposure or incandescent light heat, if moisture develops inside the plastic, there is need to allow the substrate to further air out. Several areas should be tested to be sure. Once sealer is installed protect from rain and moisture for 8 hours, as water will dull and damage the finish. Determine suitability of the surface for proper bond and prevent damage and spotting.

### **Installation:**

Stir well with a drill mixer prior to application. Install product using short nap rollers or spray equipment using a fan tip. When using rollers, apply in one direction to avoid entraining surface air and forming bubbles leaving blemishes. Apply first coat at the rate of 300– 400 Sq./Ft per gallon and allow to fully dry, then apply second coat at the same rate of application to complete installation. Product will dry to the touch in one hour. 2 thin coats are better than a thick application. Do not apply in hot sun as product will start to pull and produce a poor finish and questionable bond. Do not use when inclement weather is imminent. Test a small area prior to re-coating existing sealed areas by applying the product to observe compatible and successful bond. Do not thin.

### **Packaging and Shelf life:**

5 Gallon Pails.

Store un-open in a dry cool place away sun light, heat and ignition sources in the original package.

Shelf life is one year.

### **Compliance:**

Under <600 g/l. VOC contents.

### **Clean-up:**

Use Lacquer thinner to clean tools and equipment.

### **Safety and Disposal:**

Use adequate ventilation and do not place near sparks or flames. This product is intended for professional trades and should be handled with care. Use eye and skin protection and appropriate ventilation equipment, specially in interior spaces. Fumes can easily ignite by static and sparks. Avoid sources of ignition and breathing vapors. Do not dispose in sewers, storm drains or near water. If exposure causes illness, evacuate to fresh air and seek medical help immediately. Breathing vapors can cause nausea, headaches, dizziness and respiratory distress. Keep away from children and pets. Store in dry cool space. Check local rules for disposal. Product is solvent base. Contains Methylbenzene and Naphtha ingredients.

### **Warranty:**


When product is used according to it's intended use and directions, this warranty is limited to the refund of the purchase price if deemed defective at manufacture. Products past their shelf life or improperly stored will not be considered. This product is intended for industrial professional use by competent tradesmen with sufficient knowledge and experience on use and proper handling of these products. The purchaser agrees to assume all responsibility for product selection, use, transport and disposal of product and all packaging.

Builders Construction Products shall not assume any responsibility for product or be liable to the purchaser or any third party for costs of labor, direct, indirect or consequential damages related or due to the use or suitability of this product. No other warranties are implied. Disposal of un-used product and all packaging is the responsibility of the end user. Please review local rules for proper disposal.

Builders Construction Products  
2761 NW 19th St, Pompano Beach, FL 33069  
Tel: (954) 657-8812 Fax: (954) 657-8631

We care about the environment



**Builders**   
CONSTRUCTION PRODUCTS

Technical Data