



Paver-Lok

Paver, Stone & Brick Seal

Description and Uses:

Solvent based membrane forming sealer that enhances the color of pavers, stones and sealable clay bricks.* Provides a gloss, and protects against moisture damage, abrasion, dirt and intermittent chemical spills. Lasts longer than conventional resins. Perfect to use on driveways and most exposed areas. Prevents water penetration. Seals and consolidates the sand in the joints.

Limitations:

Product should be installed on a clean and dry surface. Turn off sprinklers 3 days before application. Once sealer is installed protect from rain and moisture for 8 hours, as water will dull the finish.

Installation:

Pavers should be reasonably dry and clean. Sand joints should be filled and compacted. Do not thin product. Install using pump spray equipment for better results. Apply first coat at the rate of 300 to 400 Sq./Ft per gallon and allow to fully dry, then apply a second coat at the same rate of application to complete installation.

Two thin coats are better than one thick coat. This product will dry to the touch in one hour.

Do not apply in direct hot sun as it can produce a poor bond on a hot surface or when inclement weather is imminent.

Test a small area prior to re-coating existing sealed areas by applying the product to observe satisfactory results.

Packaging and Storage:

5 Gallon metal pails with spout.

Store in original package in a dry cool place away from heat, sun light and ignition sources. Shelf life is one year.

Compliance:

Under <600 g/l. VOC contents.

Clean-up:

Use xylene or lacquer thinner to clean tools and equipment.

Safety:

Use adequate ventilation and do not place near sparks or

flames. This product is intended for professional use and should be handled with care. Use eye, skin and appropriate ventilation equipment, especially in interior spaces.

Fumes can easily ignite by static and sparks.

Avoid sources of ignition and inhalation of vapors and do not dispose of product in sewers, storm drains or near water.

If exposure causes illness, evacuate to fresh air and seek medical help immediately.

Use NIOSH type respirator. Inhalation of vapors can cause nausea, headaches, dizziness and respiratory distress. Keep away from children and pets. Store in a dry, cool space.

Contains strong solvents. Comply with local ordinance for rules and regulations regarding disposal.

**Some clay products can retain moisture and release salts under membrane sealers. Check with the brick manufacturer for their product sealing recommendations.*

We have other non-membrane forming options you may use on some clay bricks that do not accept membrane type sealers.



TechniColor Data

Builders Construction Products
2761 NW 19th St, Pompano Beach, FL 33069
Tel: (954) 657-8812 Fax: (954) 657-8631
www.builderscolor.com

We care about the environment



Builders 
CONSTRUCTION PRODUCTS

Warranty:

When product is used according to directions; warranty is limited to the refund of the purchase price if deemed defective at manufacture. Products exceeding their shelf life are excluded from this warranty. Products are intended for industrial professional use by competent tradesmen with sufficient knowledge and experience on their use, installation and product suitability.

Builders Construction Products shall not be liable to the purchaser or any third party for labor costs, direct or indirect, any consequential damages related or due to the use, suitability or installation of this product.

No other warranties are implied. No one is authorized, employees of Builders Const. Prods. or otherwise to make modifications or misrepresentations of any warranties other than what is expressed or covered in this published document. Purchaser and or the end user agrees to assume all responsibility for use, transport and proper disposal of un-used product and packaging. Keep from the reach of children and pets.

Do not dispose in drainage systems, lakes or bodies of water. Review MSDS for additional health information.

www.Builderscolor.com