

Loktite Acrylic Modifier Fibered Additive

Description:

Loktite Acrylic Fibered Additive is a 100% acrylic copolymer based additive with integral high performance cellulose fibers to modify and fortify concrete, mortars, grouts and other cementitious mixes. It is a thick emulsion that will dissolve into the mix to provide characteristics that mixes along will not provide. Mixes with **Loktite**, will exhibit water resistance, increased bond, higher compressive, tensile strength and dimensional stability while providing integral curing capabilities. When added according to directions, **Loktite** supplies acrylic modification on mixes up to 10% of the cementitious paste providing all of the benefits. Modified mixes also eliminate the need for surface applied bonding agents. Fibers are designed to release internal moisture to provide superior system curing.

Uses:

Used in stucco base coats and when increased performance is needed of all Portland cement type mixes, including thin toppings, underlayment, grouts and plasters going over concrete and masonry, horizontal steel and wood.

Limitations:

Always test samples of all mixed components, including added **Loktite** when considering uses as a system component in load bearing structural applications for concrete repairs, toppings, grouts, mortars, etc.

Installation:

Do not dilute. Add a one gallon unit per each bag of Cement. Gauge water to produce a cohesive and workable mix. Product will slightly accelerate the initial set of most mixes and will relax with manual mixing on the board. Consider a retarding agent or using cold water to mix if installation will require extended time when working in extreme hot weather.

Packaging:

Available in cases of 4/1 Gallon plastic bottles.

Clean-up and safety:

Product is not flammable. Clean tools and equipment with soap and water. Wear eye protection when using this product. Avoid prolonged skin contact. Product is not listed as a harmful chemical. Dispose of containers properly.

Compliance:

ASTM C-1059, Type II

Warranty: When product is used according to directions, warranty is limited to the refund of the purchase price if deemed defective at manufacture. This product is intended for industrial professional use by competent tradesmen. Builders Construction Products shall not be liable to the purchaser or any third party for costs of labor direct or indirect, and incidental or consequential damages related to the use or suitability of this product. No other warranties are implied. Responsible disposal of used products and packaging is the responsibility of the purchaser and or end user.

Builders Construction Products 2761 NW 19th St, Pompano Beach. Fl. 33069 Tel: (954) 657-8812 Fax: (954) 657-8631



