



ColorBlend® Liquid Stamp Release

Description:

Liquid Stamp Release is used as an evaporating release agent which is used when stamping polymer modified overlays.

This product provides a non stick lubricating barrier for placing the stamp mats.

Use prior to applying the imprinting tools.

Product evaporates completely allowing to seal the same day.

This product can also be tinted to produce a subtle semi-transparent transfer of coloring that provides antiquing effects.

It is especially suited for imprinting with latex type stamping mats over polymer modified overlays.

Use and Installation:

Spray a consistent wet coat with a fan tipped pump sprayer over the surface and the mat. Be careful not to splatter or pond on the surfaces.

Do not treat over treat an area and exceed the capacity to apply the imprints over the surface before the product evaporates.

Re-apply when necessary.

Packaging:

Supplied in 5 gallon metal spout pails.

Coverage:

One gallon will treat approximately 120 to 180 Sq./Ft. depending on surface profile.

Clean-up:

Clean tools and equipment with a suitable solvent-like denatured alcohol, mineral spirits or lacquer thinner followed by soap and water.

Shelf Life:

After the first use of this product it is good for up to one year only if product remains uncontaminated and is kept in a tightly sealed original container.

Safety:

Keep away from flames and sparks. Wear skin and eye protection. Do not breathe in vapors.

Use in well ventilated areas only. This product is intended for use by qualified craftsmen experienced in producing professional results.

Limitations:

Liquid Stamp Release is safe to use with most mold materials, but always test first because premature application over a very soft surface can cause surface cracking. This product is highly flammable and can burn, so please avoid use when sources of ignition sources may be present.

Precautions:

Do not dispose of this product into sewers, lakes, rivers or ponds because it is harmful to fish and wildlife. Clean spills and dispose this product in accordance with local rules and regulations. Store containers tightly closed in a cool dry place away from heating equipment or sources of sparks and excessive heat.



TECHNICAL DATA

Builders Construction Products
2761 NW 19th St, Pompano Beach, Fl. 33069
Tel: (954) 657-8812 Fax: (954) 657-8631
www.Buildercolor.com



We care about the environment

Builders 
CONSTRUCTION PRODUCTS

Warranty:

When product is used according to directions; warranty is limited to the refund of the purchase price if deemed defective at manufacture. Products exceeding their shelf life are excluded from this warranty. Products are intended for industrial professional use by competent tradesmen with sufficient knowledge and experience on their use, installation and product suitability.

Builders Construction Products shall not be liable to the purchaser or any third party for labor costs, direct or indirect, any consequential damages related or due to the use, suitability or installation of this product.

No other warranties are implied. No one is authorized, employees of Builders Const. Prods. or otherwise to make modifications or misrepresentations of any warranties, other than what is expressed or covered in this published document. Purchaser and or the end user agrees to assume all responsibility for use, transport and proper disposal of un-used product and packaging. Keep from the reach of children and pets.

Do not dispose in drainage systems, lakes or bodies of water. Review MSDS for additional health information.

Keep away from the reach of children and pets

www.BuildersColor.com