



Paver-Lok

Paver, Stone & Sand Joint Seal

Moisture Barrier

Description and Uses:

Solvent based membrane forming sealer that enhances the color of Pavers, Stones and sealable clay Bricks* Provides a gloss, protects against moisture damage, abrasion, dirt and intermittent chemical spills. Using new high performance acrylic polymers that do not yellow and last longer than conventional resins. Perfect to use on driveways and most exposed areas. Can also be used on all masonry areas to prevent water penetration. Seals and consolidates the sand joints.

Limitations:

Product should be installed on a clean and dry surface. Turn off sprinklers 3 days before application. Once sealer is installed protect from rain and moisture for 8 hours, as water will dull the finish.

Installation:

Install product using short nap rollers or spray equipment. When using rollers, apply in one direction to avoid entraining surface air and forming bubbles. Apply first coat at the rate of 300– 400 Sq./Ft per gallon and allow to fully dry, then apply second coat at the same rate of application to complete installation. Two thin coats are better than a thick coat. Product will dry to the touch in one hour. Do not apply in direct hot sun as product will start to pull and produce a poor bond on a hot surface, or when inclement weather is imminent. Test a small area prior to re-coating existing sealed areas by applying the product to observe compatible and bond. Do not thin.

Packaging and Storage:

5 Gallon Pails

Store in original package in a dry cool place away from heat, sun light and ignition sources. Shelf life is one year.

Compliance:

Under <600 g/l. VOC contents.

Clean-up:

Use Xylene or Lacquer thinner to clean tools and equipment.

Safety:

Use adequate ventilation and do not place near sparks or flames. This product is intended for professional trades and should be handled with care. Use eye, skin and appropriate ventilation equipment, specially in interior spaces. Fumes can easily ignite by static and sparks. Avoid sources of ignition and breathing vapors. Do not dispose in sewers, storm drains or near water.

If exposure causes illness, evacuate to fresh air and seek medical help immediately. Breathing vapors can cause nausea, headaches, dizziness and respiratory distress. Keep away from children and pets. Store in dry cool space. Contains Ethylbenzenes Naphtha. Check local rules for disposal.

- Not all clay bricks can be sealed with membrane sealers. Some clay bricks may effloresce vanadium and lime salts under coatings, a penetrating waterproofing system is preferred in such cases. Check our web-site for alternative products. Moisture testing is required. Allow more time to fully dry after cleaning surfaces. Consult brick manufacturer for sealing suggestions.


Warranty:

When product is used according for it's intended use and directions, this warranty is limited to the refund of the purchase price if deemed defective at manufacture. Products past their shelf life or improperly stored will not be considered. This product is intended for industrial professional use by competent tradesmen with sufficient knowledge and experience on use and proper handling of these products. The purchaser agrees to assume all responsibility for product selection, use, transport and disposal of product and all packaging. Builders Construction Products shall not assume any responsibility for product or be liable to the purchaser or any third party for costs of labor, direct, indirect or consequential damages related or due to the use or suitability of this product. No other warranties are implied. Disposal of un-used product and all packaging is the responsibility of the end user. Please review local rules for proper disposal.

Builders Construction Products
2880 NE 7th Ave, Pompano Beach. Fl. 33064
Tel: (954) 657-8812 Fax: (954) 657-8631
www.builderscolor.com

We care about the environment



Builders 
CONSTRUCTION PRODUCTS

TECHNICAL DATA