



ColorBlend[®] Concrete Stain

Description

ColorBlend[™] Stain is an emulsion of water based Epoxy-Acrylic polymers and oxide pigments, designed to go over new and old concrete to re-color or complement new colored surfaces by eliminating any color variation from inconsistent finishes and a host of other factors affecting color concrete surfaces. Provides a soft sheen finish when dry and is very durable under normal use. Can also be used on wood decks (dry) and many other substrates to provide an even colored surface. 18 standard colors are available.

Uses & Limitations:

Use on new colored concrete surfaces as a color seal coat, or over existing concrete to repair, add or change the color. Product will produce a painted look that is not supposed to replace integral or hardener type colored concrete systems in appearance. This product is intended for it's surface color enhancing and sealing qualities. Allow fresh concrete to cure for 48 hours prior to first coating.

Application and Surface preparation:

Apply to surfaces at the rate of 200 to 400 Sq./Ft per gallon (depending on profile & absorbency). Do not puddle or dilute the product. A second coat over new concrete can be applied after 7 to 14 days. On existing concrete, clean all dirt and contaminants. Apply first coat to a dry surface to allow stain to penetrate. A second coat can be applied after the first coat has dried to the touch.

Coverage

Over light textured concrete, the coverage will mostly average 200 to 400 Sq./Ft per gallon. Surface profile and absorbency will determine your true coverage. 2 thin coats are better than one heavy coat, required for best results and color.

Packaging

Available in 5 gallon pails. Custom matched colors available for an additional fee.

Safety, Clean up and Disposal:

Non-flammable emulsion. . Clean tools and equipment with soap and water Keep away from children and pets. Wear eye protection and avoid prolonged skin contact.

Compliance:

ASTM 309, ASTM 1315-Type I, class A ASTM 3359
Method A VOC <250 gm./l.

Technical Data

Warranty: When product is used according to directions, warranty is limited to the refund of the purchase price if deemed defective at manufacture. This product is intended for industrial professional use by competent tradesmen. Builders Construction Products shall not be liable to the purchaser or any third party for costs of labor direct or indirect, incidental or consequential damages related to the use or suitability of this product. No other warranties are implied. Responsible disposal of used products and packaging is the responsibility of the purchaser and or end user.

Builders Construction Products
2880 NE 7th Ave, Pompano Beach, Fl. 33064
Tel: (954) 657-8812 Fax: (954) 657-8631



We care about the environment

